

Powtran AC and DC Choke



Features

for improving power factor. 220V,380V,440V,480V,575V,690V AC input &output choke.DC choke

Applications

USing in input , output of frequency inverter!

155/130/145

Model	Voltage(V)	Power(KW)	Rated current(A)	N.W(kg)	inductance (mH)	Size	
						L/W/H(mm)	Installation a/b/d(mm)
ACL-0005-EISC-EM8B	380	1.5	5	2.48	2.0%	2.8	110/84/130
ACL-0007-EISC-E2M5B	380	2.2	7	2.54	2.0%	2.0	110/84/130
ACL-0010-EISC-E1M5B	380	3.7	10	2.67	2.0%	1.4	110/84/130
ACL-0015-EISH-E1M0B	380	5.5	15	3.45	2.0%	0.93	155/76/150
ACL-0020-EISH-EM75B	380	7.5	20	3.25	2.0%	0.7	155/76/150
ACL-0030-EISH-EM60B	380	11	30	4.12	2.0%	0.47	155/130/130
ACL-0040-EISH-EM42B	380	15		5.22	2.0%	0.35	
ACL-0050-EISH-EM35B	380	18.5	50	6.25	2.0%	0.28	155/130/145
ACL-0060-EISH-EM28B	380	22	60	6.89	2.0%	0.24	155/130/145
ACL-0080-EISC-EM19B	380	30	80	7.55	2.0%	0.17	195/130/160
ACL-0090-EISC-EM19B	380	37	90	7.55	2.0%	0.16	195/130/160

ACL-0120-EISH-EM13B	380	45	120	10.44	2.0%	0.12	195/135/160
ACL-0150-ELSH-EM11B	380	55	150	14.8	2.0%	0.095	250/155/228
ACL-0200-ELSH-E80UB	380	75	200	19.2	2.0%	0.07	250/175/228
ACL-0250-ELSH-E65UB	380	110	250	22.1	2.0%	0.056	250/175/260
ACL-0290-ELSH-E50UB	380	132	290	28.3	2.0%	0.048	290/180/270
ACL-0330-ELSH-E50UB	380	160	330	28.3	2.0%	0.042	290/180/270
ACL-0390-ELSH-E44UB	380	185	390	31.8	2.0%	0.036	320/190/270
ACL-0490-ELSH-E35UB	380	220	490	43.6	2.0%	0.028	320/220/305
ACL-0530-ELSH-E35UB	380	240	530	47	2.0%	0.026	320/240/305
ACL-0600-ELSH-E25UB	380	280	600	49	2.0%	0.023	320/240/305
ACL-0660-ELSH-E25UB	380	300	660	52	2.0%	0.021	320/240/305
ACL-0800-ELSH-E25UB	380	380	800	68.5	2.0%	0.0175	385/250/390
ACL-1000-ELSH-E14UB	380	450	1000	68.5	2.0%	0.014	385/250/390
ACL-1200-ELSH-E11UB	380	550	1250	106	2.0%	0.0011	395/325/430
ACL-1600-ELSH-E12UB	380	630	1600	110	2.0%	0.0087	395/325/430

© 2009-2010 Eurodrive Systems Limited - All rights Reserved Registered in England No : 06810696